

Technical data

Art. no.	10896	
Gauge	H0	
PIN/Interface	PluX22	
According to NEM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	658
Cable	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
DCC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
MM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Load regulation	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
POM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
NMRA compatible	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Speed steps (14, 28, 128)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Max. motor current	1.2 A	
Light and function outputs – of which outside interface	10, summary current: max. 0.8 A –	
Max. decoder sum current	1.2 A	
Short-circuit protection of all outputs	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Dimensions	22 x 15 x 3,5 mm	
RailCom®	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Complies with ZIMO article	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	MX633P22
Updatable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Breaking section support		
Lenz ABC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Märklin 72441/72442	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
ZIMO HLU	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Connection possibility for energy storage	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
Standard sound (Steam-, Diesel-, Electric locomotives)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
Loudspeaker	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	