

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Plastic glue liquid, with brush, 25 ml - item 39995

UFI: RKAC-8UMC-QSA1-53T9

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives and sealants

1.3. Details of the supplier of the safety data sheet

Company name:	Viessmann Modelltechnik GmbH	
Street:	Bahnhofstr. 2a	
Place:	D-35116 Hatzfeld-Reddighausen	
Telephone:	+49 (0) 6452 93400	Telefax: +49 (0) 6452 934019
E-mail:	info@viessmann-modell.de	
Contact person:	info@viessmann-modell.de	Telephone: +49 (0) 6452 93400
Internet:	www.viessmann-modell.de	

1.4. Emergency telephone number: Information Centre Mainz +49 (0) 6131 19240 (24h, in German and English)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

n-butyl acetate
ethyl acetate

Signal word: Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 2 of 12

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
123-86-4	n-butyl acetate			45 - < 50 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
141-78-6	ethyl acetate			30 - < 35 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
123-86-4	204-658-1	n-butyl acetate	45 - < 50 %
	dermal: LD50 = 14112 mg/kg; oral: LD50 = 12789 mg/kg		
141-78-6	205-500-4	ethyl acetate	30 - < 35 %
	dermal: LD50 = > 20000 mg/kg; oral: LD50 = > 5600 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Wash with plenty of water. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 3 of 12

5.1. Extinguishing media**Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), alcohol resistant foam, Extinguishing powder
Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.
In case of fire may be liberated: Pyrolysis products, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Evacuate area.

For non-emergency personnel

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.
Ventilate affected area.

Other information

Use non-sparking tools.
Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.
Use personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.
Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink,

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 4 of 12

smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances

Further information on storage conditions

Keep away from heat. Protect from direct sunlight. Keep in a cool, well-ventilated place.

7.3. Specific end use(s)

Adhesives and sealants

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
-	Dusts non-specific, respirable	-	4		TWA (8 h)	
-	Dusts non-specific, total inhalable	-	10		TWA (8 h)	
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	
-	Mineral Oil pure, highly & severely refined (Inhalable)	-	5		TWA (8 h)	
123-86-4	n-Butyl acetate	50	241		TWA (8 h)	
		150	723		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance			
DNEL type	Exposure route		Effect	Value
141-78-6	ethyl acetate			
Worker DNEL, acute	inhalation		systemic	1468 mg/m ³
Worker DNEL, long-term	inhalation		systemic	734 mg/m ³
Worker DNEL, acute	inhalation		local	1468 mg/m ³
Worker DNEL, long-term	inhalation		local	734 mg/m ³
Worker DNEL, long-term	dermal		systemic	63 mg/kg bw/day
Consumer DNEL, acute	inhalation		systemic	734 mg/m ³
Consumer DNEL, long-term	inhalation		systemic	367 mg/m ³
Consumer DNEL, acute	inhalation		local	734 mg/m ³
Consumer DNEL, long-term	inhalation		local	367 mg/m ³
Consumer DNEL, long-term	dermal		systemic	37 mg/kg bw/day
Consumer DNEL, long-term	oral		systemic	4,5 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 5 of 12

PNEC values

CAS No	Substance	
Environmental compartment		Value
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Freshwater (intermittent releases)		1,65 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		200 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Use eye protection according to EN 166.

Hand protection

Wear suitable gloves tested to EN374.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

Respiratory protection necessary at: Vapour/aerosol or mist formation, insufficient ventilation, exceeding exposure limit values.

IF exposed: Long-term (repeated): Wear a self-contained breathing apparatus and chemical protective clothing.

Thermal hazards

Wear anti-static footwear and clothing Flame-retardant protective clothing.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless, transparent
Odour:	like: Solvents
Odour threshold:	not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 6 of 12

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	Highly flammable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	(*) -4 °C
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	practically insoluble
Solubility in other solvents:	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	not determined
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours can form explosive mixtures with air.

Further Information

(*) ethyl acetate

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Heat. UV-radiation/sunlight.

10.5. Incompatible materials

Oxidizing agent, Pyrophoric or self-heating substances

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
123-86-4	n-butyl acetate				
	oral	LD50 mg/kg 12789	Rat	ECHA	OECD 423
	dermal	LD50 mg/kg 14112	Rabbit	ECHA	OECD 402
141-78-6	ethyl acetate				
	oral	LD50 mg/kg > 5600	Rat	ECHA	
	dermal	LD50 mg/kg > 20000	Rabbit	ECHA	

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (n-butyl acetate; ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, Skin contact, Eye contact, Inhalation.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

The product is not: Ecotoxic.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 8 of 12

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
123-86-4	n-butyl acetate						
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA	OECD 203
	Acute algae toxicity	ErC50	397 mg/l	72 h	Desmodesmus subspicatus	ECHA	
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)	ECHA	
	Algae toxicity	NOEC	200 mg/l	3 d	Desmodesmus subspicatus	ECHA	
	Crustacea toxicity	NOEC	23 mg/l	21 d	Daphnia magna (Big water flea)	ECHA	OECD 211
141-78-6	ethyl acetate						
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	ECHA	
	Acute crustacea toxicity	EC50 mg/l	1350	48 h	Daphnia magna (Big water flea)	ECHA	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
123-86-4	n-butyl acetate			
	OECD 301D	83 %	28	ECHA
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
123-86-4	n-butyl acetate	2,3
141-78-6	ethyl acetate	0,68

BCF

CAS No	Chemical name	BCF	Species	Source
123-86-4	n-butyl acetate	15		
141-78-6	ethyl acetate	30		ECHA

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 9 of 12

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: Adhesives
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 640D
Limited quantity: 5 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 5 L
Excepted quantity: E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 10 of 12

EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1133
14.2. UN proper shipping name: ADHESIVES
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable liquids! Vapours can form explosive mixtures with air.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: < 80 %

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Additional information

Observe in addition any national regulations!

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 11 of 12

Abbreviations and acronyms

Flam. Liq: Flammable liquid
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging
EU: European Union
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
REACH: Registration, Evaluation and Authorization of Chemicals
UN: United Nations
PBT: Persistent, Bioaccumulative, Toxic
SVHC: Substance of Very High Concern
vPvB: very Persistent, very Bioaccumulative
ATE: Acute Toxicity Estimates
BCF: Bio-Concentration Factor
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level
PNEC: Predicted No Effect Concentration
VOC: Volatile Organic Compounds
DIN: Deutsches Institut für Normung e.V. (German Institute for Standardization)
EN: European Standard
ISO: International Organization for Standardization
IUCLID: International Uniform Chemical Information Database
LC50: Lethal Concentration, 50 %
LD50: Lethal Dose, 50 %
LL50: Lethal Loading, 50 %
OECD: Organisation for Economic Co-operation and Development
EC50: Effective Concentration 50 %
M-Faktor: Multiplication Factor
EL50: Effect Loading, 50 %
ErC50: Effective Concentration 50 %, growth rate
M-Faktor: Multiplication Factor
NOEC: No Observed Effect Concentration
ADN: Accord européen relatif au transport international des marchandises Dangereuses par voies de Navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
DGR: Dangerous Goods Regulations
EmS: Emergency Schedules
IATA: International Air Transport Association
IBC: Intermediate Bulk Container
ICAO: International Civil Aviation Organization
IE: Industrial Emissions
IMDG: International Maritime Code for Dangerous Goods
LQ: Limited Quantity
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
MFAG: Medical First Aid Guide
RID: Regulations concerning the International carriage of Dangerous goods by rail
TI: Technical Instructions

Key literature references and sources for data

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). (v.1.2, 2013)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastic glue liquid, with brush, 25 ml - item 39995

Revision date: 28.11.2024

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)